

Investigating Neural Networks for Fault Classification in Gearboxes

Dharmender Jangra*

Department of Mechanical and Automation Engineering, Northern India Engineering College, New Delhi, India

Received 30 Sept 2022, Accepted 11 Oct 2022, Available online 18 Oct 2022, Vol.10 (Sept/Oct 2022 issue)

Abstract

The present work focuses on classifying different gearbox faults based on neural networks. Efforts are made to include all the faults and classifiers based on the neural network of transmission systems reported in the literature. Fault classification is essential for reliable and quick protective digital protection. Hence, a suitable review is needed. So, the work concentrates on the different faults in the gearbox and available neural network-based approaches reported in the field.

Keywords: Faults, Fault Classification, Transmission System, Neural Network

Introduction

The gearbox is a essential part of the transmission system and transfers motion and power. The gearbox found its application in various sectors like industrial, military and wind turbine etc.[1]. Any failure in system elements causes the system to shut down. A gearbox failure results in downtime, costly repair and living causalities[2–4]. So, it is essential to detect these faults at an early stage. Many studies have been reported in the direction of the failure of different machine elements like bearing and Gear [5-62]. Many techniques are used to design the experiments and collect the data, like Taguchi [63-77] and so on. Different techniques like vibration[78], acoustic, wear monitoring, noise signature, and temperature analysis can diagnose gearbox faults [79]. As mentioned above, vibration is used widely due to its cost-effectiveness and easy information processing [80]. The vibration signature starts changing as the faults develop in the system[4,81]. The vibration data is preprocessed to get the feature vector to train the model. In literature, many signal processing techniques are available to extract helpful information from the vibration signal. The signal processing techniques are classified into time, frequency, and time-frequency domains [82]. The signal is demodulated, noise is reduced, and valuable information is kept using the signal processing techniques. A survey of these techniques is found in the literature [79,83,84]. NASA uses the wear debris-based technique to develop a complete framework for gearbox diagnosis [85].

In literature, many algorithms are used to detect and diagnose the faults in gearboxes[86]; these are the support vector machine and neural networks. To reduce the dimensions of the failure feature vector, the technology of principal component analysis[87,88] is adopted to transform the original failure feature vector into a smaller set of variables. In literature, artificial neural networks combined with the empirical mode decomposition, fuzzy logic and support vector classification family attracted most of the attention as these results are good compared to other available methods[89]. Deep learning also succeeded in classification as it owns deeper representations for faulty features. Neural networks based on deep learning are also in practice.

This paper is structured on the different faults of the Gear and the use of different neural network-based techniques to classify the faults.

2. Failure modes of the gearbox and diagnostics

2.1 Failure modes and diagnosis

Due to its complex tribological interaction, Gear has to degrade over time. Gear failure is the function of tooth geometry, kinematics, forces, material, lubrication, and environmental characteristics. The gear tooth failure is classified based on strength and non-strength basis. The failure may occur gradually or sudden. The AGMA F14 [90] standard classifies failure into seven categories and 36 failures. In literature main focus is on the crack, pitting, flank wear and root fracture of the gears. Failure is defined as the termination of the ability of the element to perform the desired function. Failure is associated with

*Corresponding author's ORCID ID: 0000-0000-0000-0000-0000
DOI: <https://doi.org/10.14741/ijmcr/v.10.5.4>

the desired function. The failure mode describes different ways of an item's failure. The failure may be random or systematic. A failure result in the loss of production or services and safety. The failure may be detected or undetected. The failures may be design-related faults or operational errors. Detection is both localized and distributed.

Maintenance is a complex set of operations that compromise the diagnosis, scheduling, budgeting, and execution of decisions. The execution of the gearbox maintenance is a combination of planning, budgeting, and material and a group of personnel and organizations. The condition-based maintenance is a request-based upkeeping of machine availability. Timely actions are dependent upon the early detection of the damage. The damage detection process is divided into the following steps:

Step 1: Data collection

The data is measured with the help of the proper sensor like vibration, acoustic, wear debris etc. For example, the vibration sensor is mounted on the gear casing or bearing positions to measure the acceleration data of the gearbox.

Step 2: Processing

The acquired data is processed to reduce the noise and other modulation components to detect the fault feature of the Gear. For example, the vibration signal is averaged about the shaft rotation by time-synchronous averaging (TSA). Different features are extracted and stored in the feature vector from this averaged data. Further, this feature vector is reduced in the dimension by principal component analysis (PCA).

Step 3: Classification of the fault.

The reduced vector of the feature is used to train the model by using SVM or NN. The unknown vector is then given as the input, and the trained model provides the diagnostic results.

2.2 Vibration-based failure indicator

Around 90% of faults are related to the unbalancing and misalignment of the rotating parts. Two main characteristics of vibration signals are frequency and amplitude. Table 1 summarizes the vibration-based fault indicator and various gear failure modes based on time, frequency and time-frequency modes. The performance of these indicators depends on the severity of the faults.

The indicators developed or chosen for the fault diagnosis should possess the following features:

- Monotonicity - shows the trend over time
- Robustness – tolerance to the outliers

- Trendability/correlation – correlation with the other available indicators.

Table 1. Summary of fault indicator of various gear failure modes [79]

Type	Indicator	Fault identified
Time	RMS	Fault progression
	Kurtosis	Pitting
	Crest factor	Tooth fault localization
	Energy operator	Scuffing, severe pitting
	FM0	Distributed wear, tooth breakage
	NA4	Pitting
	NA4*	Progressing damage
	CCR	Pitting
	FM4	Crack, pitting
	M6A	Flank Wear
	Energy ratio	Uniform wear
Frequency	GMF harmonic amplitude	Wear
	Sideband amplitude	Pitting
	Sideband ratio	Pitting
	ALR	Crack, wear
	Cepstrum	All kinds of fault
	Spectral kurtosis	Pitting, crack
	Phase modulation	Crack
Time-frequency	NP4	All faults
	Wavelet	All faults
	EMD	All faults
	STFT	Early-stage faults
	WVD	Early-stage faults

3. Neural Network

The detection of localized and distributed defects is essential. The fault indicators are chosen to measure sure the deviation in the signature of the machinery's health. These selected fault indicators are further processed using classifier algorithms for classification based on the severity of the faults.

Preventive maintenance is used to delay the machinery shutdown. The available data is processed using data analytics and machine learning.

The fault classification techniques to classify different types of faults in the Gear, such as pitting, crack, wear etc., are classified based on the selected fault indicators. The classification approaches separate the different fault-based on some statistical criteria. For each type of failure, the evolution/ trend of a particular fault indicator may be different. Hence, so different techniques need to be applied for the classification. Table 2 summarizes the various classification approaches discussed.

Out of these techniques, Neural network-based techniques are discussed in the following text. The idea of a neural network mimics the biological nervous system. The artificial neural network (ANN) model is trained similarly to biological learning by experience. Various researchers train different types of ANN models for fault and severity classification.

Table 2. Fault classification models and used for the type of faults [79,91]

Classification Algorithm	Type of Gear	Type of fault	Fault indicator or process
Neural Network	Spur	Wear severity, tooth breakage	Wavelet
	Bevel	Crack, worn, tooth breakage	Wavelet, EMD
	Helical	Tooth breakage	Taguchi's
Fuzzy rule	Spur	Broken and worn gear tooth	Decision tree
Neuro-fuzzy	Spur	Crack	Wavelet, kurtosis, phase modulation
SVM	Spur	Pitting	Amplitude ratios of the frequency band (PCA), RMS, peak, kurtosis, average signal CC
	Planetary	Pitting	Frequency domain-based
	Compounded spur	Crack, missing tooth	% Energy of IMF of EMD
Random forest	Spur	Crack, pitting, wear, misaligned	Time-domain and frequency domain, time-frequency domain
Deep learning	Spur	Wear, pitting, crack, broken and chipped tooth	Time, frequency and time-frequency domain indicators

A neural network represents deep learning using artificial intelligence. An artificial neural network consists of various layers of interconnected artificial neurons powered by activation functions that help switch them on/off. Like traditional machine algorithms, neural nets learn specific values in the training phase. For each neuron, the inputs and random weights are compounded and a static bias value (unique to each neuron layer) is added; this is then transferred to a suitable activation function which determines the final output value. Backpropagation is used to modify the weights of the last neural network layer in order to minimise the loss function (input vs. output) after the output is created. Weights are numeric values multiplied by inputs. They are used to minimize the loss.

The different types of Neural networks are as follows[89,92–94]:

- Perceptron
- Feed-forward neural network
- Multilayer perceptron
- Convolutional neural network
- Radial basis functional neural network
- Recurrent neural network
- Long short-term memory
- Sequence to sequence models
- Modular neural network

Perceptron

Neuronal networks include several smaller units that do specific calculations in order to identify characteristics or business information in the data. Weighted inputs may be entered into the system and applies the activation function to obtain the output as the final result. It is known as a threshold logic unit. It is a binary classifier. It can be implemented with logic gates like AND, OR, or NAND. It is helpful for linearly separable problems such as Boolean AND problem. It does not work on the non-linear problem.

Feed-forward neural networks

It is used where machine learning-based classification, face recognition, computer vision where target classes are challenging to classify, and speech algorithms have limitations. The simplest systems are forward-biased. And hidden layers may or may not be present in the model. The number of the layer depends on the complexity of the function. This does not have backward propagation. Weights are static. These are less complex, easy to design, fast and speedy, and highly responsive to noisy data. It cannot be used for deep learning.

Multiple perceptron

Work better for speech recognition, machine translation, and complex classification. Has multiple layer structure. The backpropagation is allowed to reduce the loss. Self-adjustment depends on the difference between predicted outputs Vs training inputs. It can be used for deep learning purposes. The only disadvantage is a slow speed.

Convolutional neural network

It is the three-dimensional arrangement of neurons. The first layer is called the convolutional layer. Each neurone in the convolutional layer processes information. A batch-wise input is allowed to speed up the process. The network understands the images into parts and can compute these operations multiple times to complete the full image processing. Processing involves the RGB correction and pixel change. It can be used for deep learning. It works bidirectional.

Radial basis function neural networks

It is multiple category input connected to followed by a layer of RBF neurons and an output layer with one node per category. Classification is performed by measuring the input's similarities to data points from the training set where each neuron stores a prototype when new data needs to be classified by measuring the Euclidean distance between input and its prototype.

Recurrent neural networks (RNN)

It is used to backpropagate to help in predicting the output layer. The first layer is feed-forward based and uses stored information of the last layer to input into the next layer and future. It is used for text processing, grammar check, and sequential inputs and depends on the historical data. It is not easy to train such an algorithm.

Long short-term memory network

It is an updated or improved version of RNN. The gates are used to store the information. It makes the information last longer than expected.

Sequence to sequence model

It consists of two RNNs; an encoder that processes the input and a decoder that processes the output. Both can be used in similar or different parameters. The input and output data vectors must be equal.

Modular neural network

It has multiple networks that function independently and perform sub-tasks. Network work independently during the computation process. It is fast in working due to independency.

The different types of faults in Gear are used to classify different kinds of faults in the Gear. The accuracy of the ANN model was tested with several neurons 2 to 30. The number of layers which shows the slightest deviation is selected for building the structure of ANN. The optimum network structure and number of nodes are difficult to determine [89,92–96].

Conclusions

The paper has presented a summary of the different failure modes, their diagnostic indicator and neural network-based classification and different types of neural networks. The ANN can classify the defects based on other faults diagnosis techniques like acoustic, wear debris, lubrication-related parameters, etc. In a few works of literature, the oil-based neural network classification is used [97]. But they are used for the unloaded condition. So, it is essential to study the effect of load. It is also suggested to use multiple algorithms to find the best algorithm for the particular type of fault.

References

- [1]. Liang, X., Zuo, M. J., and Feng, Z., 2018, "Dynamic Modeling of Gearbox Faults: A Review," *Mech. Syst. Signal Process.*, **98**, pp. 852–876.
- [2]. Davis, J. R., 2005, *Gear Materials, Properties, and Manufacture*, ASM International.
- [3]. Hirani, H., 2016, *Fundamental of Engineering Tribology with Applications*.
- [4]. Dharmender, Darpe, A. K., and Hirani, H., 2020, *Classification of Stages of Wear in Spur Gears Based on Wear Debris Morphology*.
- [5]. Hirani, H., & Suh, N. P. (2005). Journal bearing design using multiobjective genetic algorithm and axiomatic design approaches. *Tribology International*, 38(5), 481-491.
- [6]. Hirani, H., & Verma, M. (2009). Tribological study of elastomeric bearings for marine propeller shaft system. *Tribology international*, 42(2), 378-390.
- [7]. Samanta, P., & Hirani, H. (2008). Magnetic bearing configurations: Theoretical and experimental studies. *IEEE transactions on magnetics*, 44(2), 292-300.
- [8]. Sukhwani, V. K., & Hirani, H. (2008). Design, development, and performance evaluation of high-speed magnetorheological brakes. *Proceedings of the Institution of Mechanical Engineers, Part L: Journal of Materials: Design and Applications*, 222(1), 73-82.
- [9]. Sarkar, C., & Hirani, H. (2013). Theoretical and experimental studies on a magnetorheological brake operating under compression plus shear mode. *Smart Materials and Structures*, 22(11), 115032.
- [10]. Hirani, H., Athre, K., and Biswas, S. (October 1, 1999). "Dynamically Loaded Finite Length Journal Bearings: Analytical Method of Solution." *ASME. J. Tribol.* October 1999; 121(4): 844–852. <https://doi.org/10.1115/1.2834144>
- [11]. Hirani, H., Rao, T. V. V. L. N., Athre, K., & Biswas, S. (1997). Rapid performance evaluation of journal bearings. *Tribology international*, 30(11), 825-834.
- [12]. Sukhwani, V. K., & Hirani, H. (2008). A comparative study of magnetorheological-fluid-brake and magnetorheological-grease-brake. *Tribology Online*, 3(1), 31-35.
- [13]. Muzakkir, S. M., Lijesh, K. P., & Hirani, H. (2014). Tribological failure analysis of a heavily-loaded slow speed hybrid journal bearing. *Engineering Failure Analysis*, 40, 97-113.
- [14]. Sarkar, C., & Hirani, H. (2013, February). Design of a squeeze film magnetorheological brake considering compression enhanced shear yield stress of magnetorheological fluid. In *Journal of Physics: Conference Series* (Vol. 412, No. 1, p. 012045). IOP Publishing.
- [15]. KP, L., & Hirani, H. (2014). Stiffness and damping coefficients for rubber mounted hybrid bearing. *Lubrication Science*, 26(5), 301-314.
- [16]. Rao, T. V. V. L. N., Biswas, S., Hirani, H., & Athre, K. (2000). An analytical approach to evaluate dynamic coefficients and nonlinear transient analysis of a hydrodynamic journal bearing. *Tribology transactions*, 43(1), 109-115.
- [17]. Sarkar, C., & Hirani, H. (2013). Synthesis and characterization of antifriction magnetorheological fluids for brake. *Defence science journal*, 63(4), 408.
- [18]. Hirani, H., & Samanta, P. (2007). Hybrid (hydrodynamic+ permanent magnetic) journal bearings. *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 221(8), 881-891.
- [19]. Hirani, H. (2004). Multiobjective optimization of a journal bearing using the Pareto optimality concept. *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 218(4), 323-336.
- [20]. Muzakkir, S. M., Hirani, H., Thakre, G. D., & Tyagi, M. R. (2011). Tribological failure analysis of journal bearings used in sugar mills. *Engineering Failure Analysis*, 18(8), 2093-2103.

- [21]. Hirani, H. (2016). *Fundamentals of engineering tribology with applications*. Cambridge University Press.
- [22]. Sarkar, C., & Hirani, H. (2015). Effect of particle size on shear stress of magnetorheological fluids. *Smart Science*, 3(2), 65-73.
- [23]. Sarkar, C., & Hirani, H. (2015). Development of a magnetorheological brake with a slotted disc. *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering*, 229(14), 1907-1924.
- [24]. Lijesh, K. P., & Hirani, H. (2015). Optimization of eight pole radial active magnetic bearing. *Journal of Tribology*, 137(2), 024502.
- [25]. Muzakir, S. M., Hirani, H., & Thakre, G. D. (2013). Lubricant for heavily loaded slow-speed journal bearing. *Tribology transactions*, 56(6), 1060-1068.
- [26]. Hirani, H., & Goilkar, S. S. (2009). Formation of transfer layer and its effect on friction and wear of carbon-graphite face seal under dry, water and steam environments. *Wear*, 266(11-12), 1141-1154.
- [27]. Hirani, H., Athre, K., & Biswas, S. (1998). Rapid and globally convergent method for dynamically loaded journal bearing design. *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 212(3), 207-214.
- [28]. Muzakir, S. M., Lijesh, K. P., Hirani, H., & Thakre, G. D. (2015). Effect of cylindricity on the tribological performance of heavily loaded slow-speed journal bearing. *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 229(2), 178-195.
- [29]. Lijesh, K. P., & Hirani, H. (2015). Development of analytical equations for design and optimization of axially polarized radial passive magnetic bearing. *Journal of Tribology*, 137(1), 011103.
- [30]. Lijesh, K. P., Muzakir, S. M., & Hirani, H. (2015). Experimental tribological performance evaluation of nano lubricant using multi-walled carbon nano-tubes (MWCNT). *Int J Appl Eng Res*, 10(6), 14543-14550.
- [31]. Hirani, H. (2005). Multiobjective optimization of journal bearing using mass conserving and genetic algorithms. *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 219(3), 235-248.
- [32]. Hirani, H., Athre, K., & Biswas, S. (2000). Comprehensive design methodology for an engine journal bearing. *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 214(4), 401-412.
- [33]. Desai, C., Hirani, H., & Chawla, A. (2015). Life estimation of hip joint prosthesis. *Journal of the Institution of Engineers (India): Series C*, 96(3), 261-267.
- [34]. Hirani, H., & Goilkar, S. S. (2011). Rotordynamic Analysis of Carbon Graphite Seals of a Steam Rotary Joint. In *IUTAM Symposium on Emerging Trends in Rotor Dynamics* (pp. 253-262). Springer, Dordrecht.
- [35]. Hirani, H. (2009). Online Wear Monitoring of Spur Gear. *Indian Journal of Tribology*, 4(2), 38-43.
- [36]. Kumar, P., Hirani, H., & Agrawal, A. K. (2019). Modeling and simulation of mild wear of spur gear considering radial misalignment. *Iranian Journal of Science and Technology, Transactions of Mechanical Engineering*, 43(1), 107-116.
- [37]. Sarkar, C., & Hirani, H. (2017). Experimental studies on magnetorheological brake containing plane, holed and slotted discs. *Industrial Lubrication and Tribology*, 69(2), 116-122.
- [38]. Lijesh, K. P., & Hirani, H. (2017). Design and development of permanent magneto-hydrodynamic hybrid journal bearing. *Journal of Tribology*, 139(4), 044501.
- [39]. Hirani, H. (2012). Online Condition Monitoring of high speed gears using vibration and Oil Analysis. *Thermal Fluid and Manufacturing Science*.
- [40]. Hirani, H., Athre, K., & Biswas, S. (2000). Transient trajectory of journal in hydrodynamic bearing. *Applied Mechanics and Engineering*, 5(2), 405-418.
- [41]. Sarkar, C., & Hirani, H. (2015). Synthesis and characterization of nano-particles based magnetorheological fluids for brake. *Tribology Online*, 10(4), 282-294.
- [42]. Hirani, H., & TVVLN, R. (2003). Optimization of journal bearing groove geometry using genetic algorithm. In *National Conference on Machines and Mechanism (NaCoMM)*.
- [43]. Samanta, P., & Hirani, H. (2008, January). An overview of passive magnetic bearings. In *International Joint Tribology Conference* (Vol. 43369, pp. 465-467).
- [44]. Samanta, P., Hirani, H., Mitra, A., Fernandes, B. G., & Kulkarni, A. M. (2005, December). Test setup for magnetohydrodynamic journal bearing. In *12th Nat. Conf. Machines and Mechanisms* (pp. 16-17).
- [45]. Lijesh, K. P., Muzakir, S. M., Hirani, H., & Thakre, G. D. (2016). Control on wear of journal bearing operating in mixed lubrication regime using grooving arrangements. *Industrial Lubrication and Tribology*.
- [46]. Sukhwani, V. K., Hirani, H., & Singh, T. (2007, June). Synthesis and Performance Evaluation of Magnetorheological (MR) Grease. In *74th NLGI Annual Meeting, Scottsdale, Arizona, USA*.
- [47]. Hirani, H., & Dani, S. (2005, January). Variable Valve Actuation Mechanism Using Magnetorheological Fluid. In *World Tribology Congress* (Vol. 42029, pp. 569-570).
- [48]. Talluri, S. K., & Hirani, H. (2003). Parameter Optimization Of Journal Bearing Using Genetic Algorithm. *Indian Journal of Tribology*, 2(1-2), 7-21.
- [49]. Kumar, P., & Hirani, H. (2021). Misalignment effect on gearbox failure: An experimental study. *Measurement*, 169, 108492.
- [50]. Hirani, H., & Samanta, P. (2005, January). Performance Evaluation of Magnetohydrodynamic Bearing. In *World Tribology Congress* (Vol. 42029, pp. 97-98).
- [51]. Samanta, P., & Hirani, H. (2022). On the evolution of passive magnetic bearings. *Journal of Tribology*, 144(4).
- [52]. Jangra D., Darpe, A. K., & Hirani, H. (2020, July). Classification of stages of wear in spur gears based on wear debris morphology. In *PHM Society European Conference* (Vol. 5, No. 1, pp. 9-9).
- [53]. Hirani, H., Athre, K., & Biswas, S. (1999). Journal bearing design using TKSolver. *Applied Mechanics and Engineering*, 4(spec.), 39-44.
- [54]. Nag, S., Mondal, A., Hirani, H., Bhowmik, A. D., Chattopadhyay, A., & Banerjee, P. (2022). A dual-responsive bio-amicable fluorophore for trace level recognition of Zn²⁺ and Cd²⁺: Prefatory diagnosis of neoplastic disease from urine and ALS from saliva. *Journal of Photochemistry and Photobiology A: Chemistry*, 433, 114133.
- [55]. Ghosh, S. K., Samanta, S., Hirani, H., & da Silva, C. R. V. (Eds.). (2022). *Effective Waste Management and Circular Economy: Legislative Framework and Strategies*. CRC Press.
- [56]. Patra, S., Mallisetty, P. K., Murmu, N. C., Hirani, H., & Samanta, P. (2022). Study on fracture evaluation in

- hydrogen environment in 316L stainless steel used in high pressure hydrogen tank. *Materials Today: Proceedings*.
- [57]. Nag, S., Mondal, U., Hirani, H., Chakraborty, D., Bhaumik, A., & Banerjee, P. (2022). Strategic optimization of phase-selective thermochemically amended terra-firma originating from excavation-squander for geogenic fluoride adsorption: a combined experimental and in silico approach. *Environmental Science and Pollution Research*, 1-18.
- [58]. Sadhu, K. K., Bapanapalle, C. O., Hirani, H., Mandal, N., & Sahoo, R. R. (2022). Simultaneous effect of flake powder methodology and SiC addition on the density and hardness of Al matrix. *Materials Today: Proceedings*, 66, 3897-3901.
- [59]. Banerjee, P., Hasda, R., Murmu, M., & Hirani, H. (2022). MgO as corrosion inhibitor. In *Inorganic Anticorrosive Materials* (pp. 183-210). Elsevier.
- [60]. Kumar, P., Hirani, H., & Chatterjee, A. (2021). *U.S. Patent No. 10,962,333*. Washington, DC: U.S. Patent and Trademark Office.
- [61]. Dey, D., Mondal, A., Nag, S., Mondal, U., Hirani, H., & Banerjee, P. (2021). The designed synthesis of a hydrophobic covalent polymer composite to expel toxic dyes and oil from wastewater: theoretical corroboration. *New Journal of Chemistry*, 45(11), 5165-5175.
- [62]. Chatterjee, D., Dutta, S., Mondal, B., & Hirani, H. (2020). On the Effectiveness of a "Tractor Mounted Road Sanitizing Unit" Designed to Combat COVID-19 Spread. *Journal of The Institution of Engineers (India): Series C*, 101(6), 1093-1098.
- [63]. "Polymer Composites - 2021 - Antil - An Improvement in Drilling of SiCp Glass Fiber-reinforced Polymer Matrix Composites.Pdf."
- [64]. Antil, P., Singh, S., and Singh, P. J., 2018, "Taguchi's Methodology Based Electrochemical Discharge Machining of Polymer Matrix Composites," *Procedia Manuf.*, **26**, pp. 469-473.
- [65]. Antil, P., Singh, S., and Manna, A., 2020, "Experimental Investigation During Electrochemical Discharge Machining (ECDM) of Hybrid Polymer Matrix Composites," *Iran. J. Sci. Technol. - Trans. Mech. Eng.*, **44**(3), pp. 813-824.
- [66]. Antil, P., Kumar Antil, S., Prakash, C., Królczyk, G., and Pruncu, C., 2020, "Multi-Objective Optimization of Drilling Parameters for Orthopaedic Implants," *Meas. Control (United Kingdom)*, **53**(9-10), pp. 1902-1910.
- [67]. Antil, P., Singh, S., Kumar, S., Manna, A., and Katal, N., 2019, "Taguchi and Multi-Objective Genetic Algorithm-Based Optimization during Ecdm of Sicp /Glass Fibers Reinforced Pmcs," *Indian J. Eng. Mater. Sci.*, **26**(3-4), pp. 211-219.
- [68]. Antil, P., Singh, S., and Manna, A., 2018, "SiCp/Glass Fibers Reinforced Epoxy Composites: Wear and Erosion Behavior," *Indian J. Eng. Mater. Sci.*, **25**(2), pp. 122-130.
- [69]. Antil, P., Singh, S., and Manna, A., 2019, "Analysis on Effect of Electroless Coated SiCp on Mechanical Properties of Polymer Matrix Composites," *Part. Sci. Technol.*, **37**(7), pp. 787-794.
- [70]. Antil, P., Singh, S., and Manna, A., 2018, "Genetic Algorithm Based Optimization of ECDM Process for Polymer Matrix Composite," *Mater. Sci. Forum*, **928 MSF**, pp. 144-149.
- [71]. Antil, P., 2020, "Modelling and Multi-Objective Optimization during ECDM of Silicon Carbide Reinforced Epoxy Composites," *Silicon*, **12**(2), pp. 275-288.
- [72]. Kharb, S. S., Antil, P., Singh, S., Antil, S. K., Sihag, P., and Kumar, A., 2021, "Machine Learning-Based Erosion Behavior of Silicon Carbide Reinforced Polymer Composites," *Silicon*, **13**(4), pp. 1113-1119.
- [73]. Antil, P., 2019, "Experimental Analysis on Wear Behavior of PMCs Reinforced with Electroless Coated Silicon Carbide Particulates," *Silicon*, **11**(4), pp. 1791-1800.
- [74]. Antil, P., Singh, S., and Manna, A., 2018, "Glass Fibers/SiCp Reinforced Epoxy Composites: Effect of Environmental Conditions," *J. Compos. Mater.*, **52**(9), pp. 1253-1264.
- [75]. Antil, P., Singh, S., Singh, S., Prakash, C., and Pruncu, C. I., 2019, "Metaheuristic Approach in Machinability Evaluation of Silicon Carbide Particle/Glass Fiber-Reinforced Polymer Matrix Composites during Electrochemical Discharge Machining Process," *Meas. Control (United Kingdom)*, **52**(7-8), pp. 1167-1176.
- [76]. Antil, S. K., Antil, P., Singh, S., Kumar, A., and Pruncu, C. I., 2020, "Artificial Neural Network and Response Surface Methodology Based Analysis on Solid Particle Erosion Behavior of Polymer Matrix Composites," *Materials (Basel)*, **13**(6).
- [77]. Antil, P., Singh, S., Kumar, S., Manna, A., and Pruncu, C. I., 2019, "Erosion Analysis of Fiber Reinforced Epoxy Composites," *Mater. Res. Express*, **6**(10), p. 106520.
- [78]. Kundu, P., Darpe, A. K., and Kulkarni, M. S., 2019, "A Correlation Coefficient Based Vibration Indicator for Detecting Natural Pitting Progression in Spur Gears," *Mech. Syst. Signal Process.*, **129**, pp. 741-763.
- [79]. Kundu, P., Darpe, A. K., and Kulkarni, M. S., 2020, "A Review on Diagnostic and Prognostic Approaches for Gears," *Struct. Heal. Monit.*
- [80]. Kundu, P., Darpe, A. K., and Kulkarni, M. S., 2020, "Gear Pitting Severity Level Identification Using Binary Segmentation Methodology," *Struct. Control Heal. Monit.*, **27**(3).
- [81]. Kumar, A., Antil, S. K., Rani, V., Antil, P., and Jangra, D., 2020, "Characterization on Physical , Mechanical , and Morphological Properties of Indian Wheat Crop," pp. 1-18.
- [82]. Jardine, A. K. S., Lin, D., and Banjevic, D., 2006, "A Review on Machinery Diagnostics and Prognostics Implementing Condition-Based Maintenance," *Mech. Syst. Signal Process.*, **20**(7), pp. 1483-1510.
- [83]. Randall, R. B., 2011, *Vibration-Based Condition Monitoring*, John Wiley & Sons Ltd.
- [84]. Aherwar, A., 2012, "An Investigation on Gearbox Fault Detection Using Vibration Analysis Techniques: A Review," *Aust. J. Mech. Eng.*, **10**(2), pp. 169-183.
- [85]. Dempsey, and J., P., 2003, "Integrating Oil Debris and Vibration Measurements for Intelligent Machine Health Monitoring. Degree Awarded by Toledo Univ., May 2002," (March).
- [86]. Verma, A., Zhang, Z., and Kusiak, A., 2013, "Modeling and Prediction of Gearbox Faults With Data-Mining Algorithms," *J. Sol. Energy Eng.*, **135**(3), p. 031007.
- [87]. Loutas, T. H., Roulias, D., Pauly, E., and Kostopoulos, V., 2011, "The Combined Use of Vibration, Acoustic Emission and Oil Debris on-Line Monitoring towards a More Effective Condition Monitoring of Rotating Machinery," *Mech. Syst. Signal Process.*, **25**(4), pp. 1339-1352.
- [88]. Tumer, I. Y., and Huff, E. M., 2003, "Analysis of Triaxial Vibration Data for Health Monitoring of Helicopter Gearboxes," *J. Vib. Acoust.*, **125**(1), p. 120.
- [89]. Chen, Z., Li, C., and Sanchez, R., 2015, "Gearbox Fault Identification and Classification with Convolutional Neural Networks," **2015**.
- [90]. American Gear Manufacturers Association, 2014,

- "ANSI/AGMA1010-F14: Appearance of Gear Teeth - Terminology of Wear and Failure," **14**, p. 89.
- [91]. Jayaswal, P. & A. K. W., 2015, "Application of Artificial Neural Networks, Fuzzy Logic and Wavelet Transform in Fault Diagnosis via Vibration Signal Analysis: A Review," *Aust. J. Mech. Eng.*, **7**(2), pp. 157–171.
- [92]. Prasad, A., Edward, J. B., and Ravi, K., 2018, "A Review on Fault Classification Methodologies in Power Transmission Systems : Part — I," *J. Electr. Syst. Inf. Technol.*, **5**(1), pp. 48–60.
- [93]. Prasad, A., Edward, J. B., and Ravi, K., 2018, "A Review on Fault Classification Methodologies in Power Transmission Systems : Part-II," *J. Electr. Syst. Inf. Technol.*, **5**(1), pp. 61–67.
- [94]. Rafiee, J., Arvani, F., Harifi, A., and Sadeghi, M. H., 2007, "Intelligent Condition Monitoring of a Gearbox Using Artificial Neural Network," **21**, pp. 1746–1754.
- [95]. Chen, Z., Li, C., and Sánchez, R., 2015, "1684 . Multi-Layer Neural Network with Deep Belief Network for Gearbox Fault Diagnosis," pp. 2379–2392.
- [96]. Dalstein, T., and Kulicke, B., 1995, "Neural Network Approach to Fault Classification for High Speed Protective Relaying," **10**(2), pp. 1002–1011.
- [97]. Kalkat, M., 2015, "Investigations on the Effect of Oil Quality on Gearboxes Using Neural Network Predictors," **2**(April 2013), pp. 99–109.